

classi seal[®]

Installation Time 5 mins.
Tiling can begin Immediately.

'Ideal for finishing with wall panels'

Winner of
housebuilding
innovation
awards
2008

HOUSING PRODUCT OF THE YEAR

With multiple innovation awards, Classi Seal is a professional, patented waterproofing solution applied by hand to the wall facing sides of shower trays or baths prior to installation. The inherent flexibility of the product can accommodate 15mm of movement, making it equally suitable for new build, repair or renovation. Classi Seal consists of a flexible upstand made from ethylene propylene diene monomer (EPDM) and a modified butyl rubber adhesive. The EPDM is extruded with an integral antistretch glass fibre reinforcing strip. This aids speed and ease of fitting, and also allows for subsequent manipulation in the corners to assist with the tiling operation. Classi Seal is supplied in a range of lengths to match standard shower tray and bath sizes and is used in an unbroken, continuous run.



STEP 1

Thoroughly roughen and clean the sides of the tray or bath that the Classi Seal is to be attached.

STEP 2

Remove the backing paper 100mm at a time. Align the top edge of the adhesive strip with the top edge of the shower tray or bath and firmly press on by hand.

STEP 3

Manipulate and widen the upstand at corners. Upstand is easy to manipulate by hand to fit into irregular internal corners which are not square, so as not to interfere with the tiling.

STEP 4

Tiling can begin immediately.

Following tiling or wall panelling, finish with a Neutral Cure Sanitary Grade 100% Silicone.

Classi Seal prevents water leakage from around shower trays and baths caused by the inevitable shrinkage and movement within buildings.

Classi Seal is available in 2m, 2.5m, 3.2m and 4m rolls.

